

## Force Sensor KM115e 100kN/010

Item number: 5364



The force sensor KM 115 is a membrane force sensor for measuring compressive forces. It is fastened to an even surface with four screws M12. A spherical cap with a radius of 160 mm is provided for the force transmission.


The force sensor KM115e is a membrane-type force sensor for measurement of compressive forces. The integrated electronic GSV-15L provides an output signal 0...10 Volt or 4...20mA proportional to the applied force on the constructional element. The electronic GSV-15L offers a digital input for automatic zero adjustment, a digital input for autoscale and a digital output as threshold switch.

Environmental protection is IP 67.

### Optional special version

- Protection class IP68: from rated force 200 N
- Pressure range up to 8 bar
- Suitable for cleanrooms

## Technical Drawing



## Technical Data

Basic Data		Unit
Type	Force load cell	
Force direction	Compression	
Rated force F <sub>x</sub>	100	kN
Force introduction	Load button	
Dimension 1	Ø32	
Sensor Fastening	Circular ring	
Dimension 2	Ø111x21,5	
Operating force	150	%FS
Rated displacement	0.08	mm
Lateral force limit	50	%FS
Material	Stainless steel	
Dimensions	Ø115 mm x 60 mm	
Height	60	mm
Length or Diameter	115	mm
Variants	50kN...200kN	
Electrical Data		Unit

Accuracy Data		Unit
Accuracy class	0,5	
Relative linearity error	0.1	%FS
Relative zero signal hysteresis	0.05	%FS
Temperature effect on zero signal	0.02	%FS/K
Temperature effect on characteristic value	0.02	%RD/K
Relative creep	0.1	%FS
Analog Output		Unit
Voltage output from	0	V
Voltage output to	10	V
Zero adjustment to	0	V
Supply		Unit
Supply voltage from	14	V
Supply voltage to	30	V
Environmental Data		Unit
Rated temperature range from	-10	°C
Rated temperature range to	70	°C
Operating temperature range from	-10	°C
Operating temperature range to	85	°C
Storage temperature range from	-10	°C
Storage temperature range to	85	°C
Environmental protection	IP67	

Abbreviation: RD: „Reading“; FS: „Full Scale“;1) The exact nominal sensitivity is indicated in the test report;

## Pin Assignment

Channel	Symbol	Description	Wire color	PIN
	Ub	Supply voltage (depends on variant)	brown	
	GND	Ground power supply	white	
	Ua (Out)	Output signal 4... 20mA / 0... 10V / 0... 5V	green	
	Tara (Ta)	Control input for zero balance	yellow	
	Scale (Sc)	Control input for amplification factor	grey	
	GND	Ground, signal	pink	
		Shield	transparent	