

## KL500 $\pm 100\text{kN}$ , $\pm 200\text{kN}$ , $\pm 500\text{kN}$ , $\pm 1\text{MN}$



### Description

Tension load cells are ideal force sensors to measure large loads. Therefore, these are mainly used in cranes and other rope-operated lifting systems for measuring the tensile force. The load tabs have been specifically designed for use in harsh environmental conditions.

### Applications:

- Monitoring of rope forces
- Calibration of force-measuring devices

### Versions

with integrated electronics 0 ... 10V, 4 ... 20mA, Bluetooth;



## Technical Data

### Kraftsensoren

Type	Force sensor
Force direction	Tension / Compression
Force introduction	Zylinder
Operating force	100 %FS
Material	Tool steel
Surface	electrogalvanized

### Elektrische Daten

Input resistance	700 Ohm
Tolerance input resistance	30 ±
Output resistance	700 Ohm
Tolerance output resistance	30 ±
Insulation resistance	2x10 <sup>9</sup> Ohm
Rated range of excitation voltage f	2.5 ... 5 V
Operating range of excitation voltage f	1 ... 10 V
Zero signal	0.05 mV/V
Rated output	1 mV/V / FS

### Precision

Accuracy class	0,5%
Relative linearity error	0.1 %FS
Relative zero signal hysteresis	0.05 %FS
Temperature effect on zero signal	0.02 %FS/K
Temperature effect on characteristic value	0.02 %RD/K
Relative creep	0.1 %FS

### Connection Data

Connection type	Connector
Name of the connection	round plug connector M8 or M12, 4-pole, male

### Temperature

Rated temperature range f	-10 ... 70 °C
Operating temperature range f	-10 ... 85 °C



Storage temperature range f	-10 ... 85 °C
Environmental protection	IP66

Abbreviation: RD: „Reading“; FS: „Full Scale“;





1) The exact nominal sensitivity is indicated in the test report;



## Pin Configuration

Channel	Symbol	Description	Wire colour	PIN
	+Us	positive bridge supply	brown	1
	-Us	negative bridge supply	white	2
	+Ud	positive bridge output	blue	3
	-Ud	negative bridge output	black	4

## accessories

	Description	Description
	Calibration Certificate kn/200/5	Factory calibration certificate for force to 200 kN in accordance with DIN EN ISO / IEC 17025 for test materials monitoring according to DIN ISO 9001: 2008 with 5 load levels and 3 series of measurements.
	GSV-3BT M12	Measurement amplifier with wireless interface via Bluetooth®. Integrated Accu 2,6Ah for 12h;
	GSV-3BT SD	Measuring Amplifier with wireless interface via Bluetooth® for sensors with strain gauges. Configurable for the connection of full, half and quarter bridges. Input Sensitivity 2.0 mV / V.
	GSV-6K	analog amplifier pcb for sensors with strain gauges. Analog output configurable; sampling frequency is 10Hz ... 25kHz, input sensitivity adjustable 0.1 mV / V ... 8 mV / V