









K6D fastening elements and tightening torques

K6D	Type	Nominal force/ Nominal torque	Dimensions	Material	Measuring platform / Live End			Stator / Dead End		
					Thread	Tightening Torque (Nm)	Cylinder pin Hole (mm)	Thread / Cylinderhead Screw	Tightening Torque (Nm)	Cylinder pin Hole (mm)
	K6D27	±50N/1Nm	Ø27 mm x 25 mm	stainless steel/ aluminium	internal thread 6x M2x0,4 depth 4 mm	0,4	Ø2 E7 depth 4 mm	internal thread 6x M2x0,4 depth 4 mm	0,4	Ø2 E7 depth 4 mm
	K6D154	±50N/5Nm ±100N/10Nm	Ø154 mm x 100 mm	aluminium alloy	internal thread 6x M6x1 depth 8 mm	10	Ø6 E7 depth 8 mm	internal thread 6x M6x1 depth 8 mm	10	Ø6 E7 depth 8 mm
		±200N/20Nm ±500N/50Nm				15			15	
	K6D40	±200N/5Nm	Ø60 mm x 40 mm	aluminium, stainless steel mounting	internal thread 6x M5x0,8 depth 6 mm	5	Ø3 E7 depth 7 mm	internal thread 6x M5x0,8 depth 6 mm	5	Ø3 E7 depth 7 mm
		±500N/20Nm		stainless steel, stainless steel mounting		9			9	
	K6D68	±1kN/20Nm ±2kN/50Nm	Ø83 mm x 64 mm	aluminium alloy	internal thread 6x M10x1,5 depth 12 mm	40	2 x Ø6 H7 depth 12 mm	internal thread 6x M10x1,5 depth 12 mm	40	2 x Ø6 H7 depth 12 mm
		±5kN/50Nm ±10kN/500Nm		stainless steel		70			70	
	K6D80	±1kN/50Nm ±2kN/100Nm	Ø80 mm x 50 mm	aluminium alloy	internal thread 6x M8x1,25 depth 9 mm	20	2 x Ø5 E7 depth 6 mm	internal thread 6x M8x1,25 depth 9 mm	20	2 x Ø5 E7 depth 6 mm
		±5kN/250Nm		stainless steel		40			40	
	K6D110	±4kN/250Nm	Ø110 mm x 60 mm	aluminium alloy	internal thread 6x M10x1,5 depth 10 mm	50	2x Ø6 E7 depth 10 mm	internal thread 6x M10x1,5 depth 10 mm	50	2x Ø6 E7 depth 10 mm
		±10kN/750Nm		stainless steel		70			70	

K6D	Type	Nominal force/ Nominal torque	Dimensions	Material	Measuring platform / Live End			Stator / Dead End		
					Thread	Tightening Torque (Nm)	Cylinder pin Hole (mm)	Thread / Cylinderhead Screw	Tightening Torque (Nm)	Cylinder pin Hole (mm)
	K6D130	±5kN/500Nm	Ø130 mm x 80 mm	aluminium alloy	internal thread 6x M12x1,75 depth 15 mm	80	2x Ø8 E7 depth 15 mm	internal thread 6x M12x1,75 depth 15 mm	80	2x Ø8 E7 depth 15 mm
		±15kN/1.2kNm		stainless steel		120			120	
	K6D175	±10kN/1kNm ±20kN/2kNm ±50kN/5kNm	Ø175 mm x 110 mm	stainless steel, stainless steel mounting	internal thread 6x M16x2 depth 25 mm	250	2x Ø10 E7 depth 25 mm	internal thread 6x M16x2 depth 25 mm	250	2x Ø10 E7 depth 25 mm

ME-Meßsysteme GmbH
 Neuendorfstr. 18a
 16761 Hennigsdorf

Tel.: +49 3302 89824 60
 Fax: +49 3302 89824 69

Mail: info@me-systeme.de
 Web: www.me-systeme.de